

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/008306 A1

(51) International Patent Classification?: **G02B 6/16**

(74) Agents: LEE, Sang-Yong et al.; 41st, Byukcheon Bldg.,
1597-5, Seocho-dong, Seocho-gu, Seoul 137-876 (KR).

(21) International Application Number:
PCT/KR2003/002006

(81) Designated States (*national*): AE, AG, AI, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GI,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:
30 September 2003 (30.09.2003)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0050740 23 July 2003 (23.07.2003) KR

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): LG CA-
BLE LTD. [KR/KR]; 19-20F ASEM Tower, 159 Samsung-
dong, Gangnam-gu, Seoul 135-090 (KR).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): PARK, Hye-Young
[KR/KR]; 19-16 Namsan-dong 2-ga, Jung-gu, Seoul
100-042 (KR). MOON, Joon-Ho [KR/KR]; 102-905
Woorim Apt., Taeon-eup, Hwaseong-si, Gyeonggi-do
445-970 (KR).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: OPTICAL FIBER SUITABLE FOR HIGH-SPEED LARGE-SCALE WDM SYSTEM, OPTICAL TRANSMISSION
LINE AND OPTICAL TRANSMISSION SYSTEM USING THE SAME



(57) Abstract: Disclosed is a single-mode optical fiber suitable for and optical transmission line used in WDM (Wavelength Division Multiplexing) system, which has low dispersion slope, sufficient dispersion value and large effective section area over S-, C- and L- band (1460~1625nm) to enable high-speed, large-capacity signal transmission. The optical fiber uses the wavelength region from 1460 to 1625nm, and the optical fiber also has a dispersion value of 0.1~3.0ps/nm-km, more preferably 0.3~2.4ps/nm-km, at 1460nm, a dispersion value of 3.0~5.5ps/nm-km, more preferably 3.2~5.2ps/nm-km, at 1550nm, and a dispersion value of 4.5~8.0ps/nm-km, more preferably 4.8~7.7ps/nm-km, at 1625nm. In addition, the optical fiber has a dispersion slope of 0.023~0.05ps/nm-km² at 1550nm, an effective sectional area of 35~50μm² at 1550nm, an effective section area of 35~50μm² at 1460nm. Thus, though the signal is transmitted through S-, C- and L- band, this optical fiber may suppress nonlinear phenomenon and signal distortion to the minimum.